

Miniature Fans and Blowers

Powering Air for Pick and Place



Pick and Place Applications

Pick and place machines are often an integral part in a goods manufacturing process. They are designed to position manufactured goods accurately and efficiently in a particular order through an alternating application of vacuum and pressure.

Due to a geometric compact and simple design, Micronel blowers are used for this process and therefore replace traditional compressed air.



Industrial solutions must be cost-effective and robust and have a long service life. The powerful axial and radial blowers from Micronel meet all these demands. Micronel blowers are used wherever sophisticated pressure and vacuum applications are needed. Typical areas of use with negative pressure are pick & place processes, vacuum conveyor technology, vacuum clamping plates, vacuum tables or anywhere requiring the extraction of dirt particles or fluids. Negative pressure or vacuum is used in manufacturing processes to fixate or transport production goods.

Micronel's precision-made miniature blowers are impressive due to their compact design and the use of the latest brushless motor technology in order to combine high pressure or negative pressure with high airflows. A low noise level, minimal energy consumption paired with unsurpassed reliability and an optimal service life distinguish the powerful Micronel products.



U51DL

Super-compact, powerful blower in highest quality! Supply voltage12 and 24 V_{DC} Static pressure5 400 Pa

Freeflow 500 I/min

Motor controller Integrated driver

electronics



U85MX

Efficient high-performance blower for high pressure conditions!

Supply voltage 21 V_{DC}

Static pressure 12 300 Pa

Freeflow 860 I/min

Motor controller With/without integrated driver

electronics available



U100HL

Super ruggedized industrial, versatile blower!

Supply voltage 24 V_{DC} Static pressure 11400 Pa

Freeflow 865 I/min

Motor controller Integrated driver

electronics



U100H4

The industrial power blower – robust, powerful and versatile!

Supply voltage 24 V_{DC}
Static pressure 18 000 Pa
Freeflow 860 I/min

Motor controller Integrated driver

electronics